



Premium Features:

- Comfort Drive™ steering assist system with variable driver's effort control feature
- Automatic heated moisture ejectors with color-coded lanyards
- Side-mounted service center
- Connected Coach™ digital dash display
- Variable Geometry Turbo (VGT), exhaust brake
- 10,000 lb towing capacity
- SMART steering wheel with leather finish & phone controls
- Suspended adjustable pedals

Spartan Advanced Protection System® (APS)

- Spartan Safe Haul™ The industry's only factory-chassis integrated air supply for tow vehicle brake systems.

Specifications:

Engine

Cummins B6.7
 18.7 CFM Air Compressor
 750 Watt Block Heater
 Peak HP: 360 hp @ 2,400 RPM
 Peak Torque: 800 lb-ft @ 1,800 RPM

Transmission

Allison 3000MH

Chassis Ratings

34' GVWR: 35,400 lb
 37' GVWR: 38,000 lb
 34' Front GAWR: 12,400 lb
 37' Front GAWR: 14,000 lb
 34' Rear GAWR: 23,000 lb
 37' Rear GAWR: 24,000 lb
 34' GCWR: 45,400 lb
 37' GCWR: 48,000 lb

Suspension

34' Front: Integrated front air suspension and steer axle system with 12,400 lb capacity
 37' Front: Integrated front air suspension and steer axle system with 14,600 lb capacity
 Rear: Non-torque reactive parallelogram air suspension with 24,000 lb capacity

Bilstein Shocks

Front: 46 mm
 Rear: 46 mm
 Tag: 46 mm

Brakes

ABS: WABCO 4S/4M
 Front: Air disc
 Drive: Air drum

Steering

Comfort Drive steering assist system for smoother, more precise steering
 Column: Comfort Drive w/ tilt & telescope

Fuel System

Fuel Tank: 100 gallon with dual side fill
 DEF Tank: 10 gallon, driver's side fill

Electrical System

12v electrical system
 Batteries: Two 950 CCA
 Alternator: 210 amp

Cooling System

Rear-mounted radiator: parallel airflow system with low-profile radiator

Frame

Raised rail design for frame strength and basement storage

Tires

34': Michelin X Multi Z 275/70R22.5 LRJ
 37': Michelin XRV 305/70R22.5 LRL

Wheels

(4) Aluminum wheels with Accu-Shield® finish and dress kit
 (2) Steel wheels on inside dual wheels

Wheelbase

34': 206"
 37': 242"



Premium Features:

- Comfort Drive™ steering assist system with variable driver's effort control feature
- Automatic heated moisture ejectors with color-coded lanyards
- Side-mounted service center
- Connected Coach™ digital dash display
- Passive steer tag axle
- 3-stage engine compression brake
- 15,000 lb towing capacity
- SMART steering wheel with leather finish & phone controls
- Suspended adjustable pedals

Spartan Advanced Protection System® (APS)

- Spartan Safe Haul™ The industry's only factory-chassis integrated air supply for tow vehicle brake systems.

Specifications:

Engine

Cummins L9
 18.7 CFM Air Compressor
 1000 Watt Block Heater
 Peak HP: 400 hp @ 2100 RPM
 Peak Torque: 1250 lb-ft @ 1400 RPM

Transmission

Allison 3000MH

Chassis Ratings

40' GVWR: 44,200 lb
 43' GVWR: 46,000 lb
 40' Front GAWR: 14,200 lb
 43' Front GAWR: 16,000 lb
 Rear GAWR: 20,000 lb
 Tag GAWR: 10,000 lb
 40' GCWR: 59,200 lb
 43' GCWR: 61,000 lb

Suspension

40' Front: Integrated front air suspension and steer axle system with 14,600 lb capacity
 43' Front: Integrated front air suspension and steer axle system with 16,000 lb capacity
 Rear: Non-torque reactive parallelogram air suspension with 20,000 lb capacity
 Tag: Parallelogram air suspension and integrated passive steering tag axle with 10,000 lb capacity

Bilstein Shocks

Front: 46 mm
 Rear: 46 mm
 Tag: 46 mm

Brakes

ABS: WABCO 6S/6M
 Front: Air disc
 Drive: Air drum
 Tag: Air drum

Steering

Comfort Drive steering assist system for smoother, more precise steering
 Column: Comfort Drive w/ tilt & telescope

Fuel System

Fuel Tank: 100 gallon with dual side fill
 DEF Tank: 10 gallon, driver's side fill

Electrical System

12v electrical system
 Batteries: Two 950 CCA
 Alternator: 210 amp

Cooling System

Rear-mounted radiator: parallel airflow system with low-profile radiator

Frame

Raised rail design for frame strength and basement storage

Tires

40': Michelin X XRV 305/70R22.5 LRL
 43': Michelin X Line Energy Z 315/80R22.5 LRL

Wheels

(6) Aluminum wheels with Accu-Shield® finish and dress kit
 (2) Steel wheels on inside dual wheels

Wheelbase

40' 245" + 48" tag
 43' 281" + 48" tag