



2023 SPEC SHEET

Newmar Ventana

Floor plans: 3407, 3412

5-STAR FEATURES



BRAKE SYNC

Factory-installed, factory-warranted integrated air supply for your tow vehicle brake system

DRIVETECH

Wheel and column controls pair with OptiView to put every command in easy reach  
All-new ergonomic steering wheel  
Prioritizes driver safety

V RIDE

Increased towing capacity  
Superior roll stability & handling  
Greater durability & longevity



24/7 factory-direct phone support

ENGINE

Make	Cummins B6.7
Horsepower	360 HP @ 2,600 rpm
Torque	800 lb/ft
Brake	VGT (Variable Geometry Turbocharger) Brake (single stage)

WEIGHT RATINGS

Front GAWR	14,000 lbs
Rear GAWR	23,000 lbs
Tag GAWR	N/A
Total GVWR	37,000 lbs
Total GCWR	47,000 lbs

TRANSMISSION

Type	Automatic
Gears	Allison 3000 6-speed

FUEL

Type	Diesel
Fuel Tank	100 Gallon
Def Tank	10 Gallon

SUSPENSION

Front	NEWAY
Wheel Cut	55 Degree front wheel
Rear	V-Ride

SHOCKS

Make	Sachs custom tuned
------	--------------------

AXLES

Front	Detroit DA-F-14.7-3
Rear	Detroit DA-RS-23.0-4

BRAKES

Front	Bendix Air Disc Brakes with ABS
Rear	Meritor Air Drum Brakes with ABS

COOLING

Radiator	1,335 sq/inch, Rear mounted
----------	-----------------------------

RAILS

Front	9.0" x 2.75" x 0.25"
Upper	9.0" x 2.75" x 0.25"
Rear	9.0" x 2.75" x 0.25"

FRAME

Construction	Raised rail with lowered rear section
Wheel Base	206"

HITCH

Rating	5,000 lbs
--------	-----------

TIRES

Make	Michelin XRV
Front Size	305/70R 22.5 20-ply
Rear Size	305/70R 22.5 20-ply
Wheels	8.25" Aluminum

ELECTRICAL

Alternator	240 Amp Leece-Neville
Battery	(2) 1,900 CCA @ 0 degrees F

CONTROLS

Steering Column	Column Drive with Tilt/Telescopic
Steering Wheel	DriveTech steering wheel with dash controls
Instruments	OptiView LCD display
Safety	Mobileye Sensor Detection

WARRANTY

Basic Chassis / Drivetrain	5 years, 100,000 mi
Engine	5 years, 100,000 mi
Transmission	5 years, 200,000 mi
Battery	1 year, 100,000 mi
Corrosion / Brightwork	6 months unlimited
Frame Rails / Cross Member	5 years, 100,000 mi





2023 SPEC SHEET

Newmar Ventura

Floor plans: 3709, 3717

5-STAR FEATURES



BRAKE SYNC

Factory-installed, factory-warranted integrated air supply for your tow vehicle brake system

DRIVETECH

Wheel and column controls pair with OptiView to put every command in easy reach  
All-new ergonomic steering wheel  
Prioritizes driver safety

V RIDE

Increased towing capacity  
Superior roll stability & handling  
Greater durability & longevity



24/7 factory-direct phone support

ENGINE

Make	Cummins B6.7
Horsepower	360 HP @ 2,600 rpm
Torque	800 lb/ft
Brake	VGT (Variable Geometry Turbocharger) Brake (single stage)

WEIGHT RATINGS

Front GAWR	14,200 lbs
Rear GAWR	24,000 lbs
Tag GAWR	N/A
Total GVWR	38,200 lbs
Total GCWR	48,200 lbs

TRANSMISSION

Type	Automatic
Gears	Allison 3000 6-speed

FUEL

Type	Diesel
Fuel Tank	100 Gallon
Def Tank	10 Gallon

SUSPENSION

Front	NEWAY
Wheel Cut	54 Degree front wheel
Rear	V-Ride

SHOCKS

Make	Sachs custom tuned
------	--------------------

AXLES

Front	Detroit DA-F-14.7-3
Rear	Detroit DA-RS-23.0-4

BRAKES

Front	Bendix Air Disc Brakes with ABS
Rear	Bendix Air Drum Brakes with ABS

COOLING

Radiator	1,335 sq/inch, Rear mounted
----------	-----------------------------

RAILS

Front	9.0" x 2.75" x 0.25"
Upper	9.0" x 2.75" x 0.25"
Rear	9.0" x 2.75" x 0.25"

FRAME

Construction	Raised rail with lowered rear section
Wheel Base	242"

HITCH

Rating	5,000 lbs
--------	-----------

TIRES

Make	Michelin XRV
Front Size	305/70R 22.5 20-ply
Rear Size	305/70R 22.5 20-ply
Wheels	8.25" Aluminum

ELECTRICAL

Alternator	240 Amp Leece-Neville
Battery	(2) 1,900 CCA @ 0 degrees F

CONTROLS

Steering Column	Column Drive with Tilt/Telescopic
Steering Wheel	DriveTech steering wheel with dash controls
Instruments	OptiView LCD display
Safety	Mobileye Sensor Detection

WARRANTY

Basic Chassis / Drivetrain	5 years, 100,000 mi
Engine	5 years, 100,000 mi
Transmission	5 years, 200,000 mi
Battery	1 year, 100,000 mi
Corrosion / Brightwork	6 months unlimited
Frame Rails / Cross Member	5 years, 100,000 mi





2023 SPEC SHEET

# Newmar Ventura Tag

Floor plans: 4326, 4369, 4334, 4310, 4328

## 5-STAR FEATURES



24/7 factory-direct phone support

### BRAKE SYNC

Factory-installed, factory-warranted integrated air supply for your tow vehicle brake system

### DRIVETECH

Wheel and column controls pair with OptiView to put every command in easy reach

All-new ergonomic steering wheel  
Prioritizes driver safety

### ULTRA STEER

Reduced curb-to-curb turning radius

Eliminates costly tire scrub

Fully integrated & precision tuned to coach model & floorplan

### V RIDE

Increased towing capacity

Superior roll stability & handling

Greater durability & longevity

### ENGINE

Make	Cummins L9
Horsepower	400 HP @ 2,100 rpm
Torque	1,250 lb/ft
Brake	Engine Compression Brake (three stage)

### WEIGHT RATINGS

Front GAWR	15,600 lbs
Rear GAWR	20,000 lbs
Tag GAWR	10,000 lbs
Total GVWR	45,600 lbs
Total GCWR	60,600 lbs

### TRANSMISSION

Type	Automatic
Gears	Allison 3000 6-speed

### FUEL

Type	Diesel
Fuel Tank	100 Gallon
Def Tank	13 Gallon

### SUSPENSION

Front	NEWAY
Wheel Cut	50 Degree front wheel
Rear	V-Ride

### SHOCKS

Make	Sachs custom tuned
------	--------------------

### AXLES

Front	Detroit DA-F-15.6
Rear	Detroit DA-RS-21.0-4
Tag	UltraSteer

### BRAKES

Front	Bendix Air Disc Brakes with ABS
Rear	Meritor Air Drum Brakes with ABS

### COOLING

Radiator	1,335 sq/inch, Rear mounted
----------	-----------------------------

### RAILS

Front	9.0" x 2.75" x 0.25"
Upper	9.0" x 2.75" x 0.25"
Rear	9.0" x 2.75" x 0.25"

### FRAME

Construction	Raised rail with lowered rear section
Wheel Base	281"

### HITCH

Rating	15,000 lbs
--------	------------

### TIRES

Make	Michelin X Line Energy Z
Front Size	315/80R 22.5 20-ply
Rear Size	315/80R 22.5 20-ply
Tag Size	315/80R 22.5 20-ply
Wheels	9.00" Aluminum

### ELECTRICAL

Alternator	240 Amp Leece-Neville
Battery	(2) 1,900 CCA @ 0 degrees F

### CONTROLS

Steering Column	Column Drive with Tilt/Telescopic
Steering Wheel	DriveTech steering wheel with dash controls
Instruments	OptiView LCD display
Safety	Mobileye Sensor Detection

### WARRANTY

Basic Chassis / Drivetrain	5 years, 100,000 mi
Engine	5 years, 100,000 mi
Transmission	5 years, 200,000 mi
Battery	1 year, 100,000 mi
Corrosion / Brightwork	6 months unlimited
Frame Rails / Cross Member	5 years, 100,000 mi





2023 SPEC SHEET

# Newmar Ventura Tag

Floor plans: 4037, 4068

## 5-STAR FEATURES



24/7 factory-direct phone support

### BRAKE SYNC

Factory-installed, factory-warranted integrated air supply for your tow vehicle brake system

### DRIVETECH

Wheel and column controls pair with OptiView to put every command in easy reach

All-new ergonomic steering wheel  
Prioritizes driver safety

### ULTRA STEER

Reduced curb-to-curb turning radius

Eliminates costly tire scrub

Fully integrated & precision tuned to coach model & floorplan

### V RIDE

Increased towing capacity

Superior roll stability & handling

Greater durability & longevity

### ENGINE

Make	Cummins L9
Horsepower	400 HP @ 2,100 rpm
Torque	1,250 lb/ft
Brake	Engine Compression Brake (three stage)

### WEIGHT RATINGS

Front GAWR	14,200 lbs
Rear GAWR	20,000 lbs
Tag GAWR	10,000 lbs
Total GVWR	44,200 lbs
Total GCWR	59,200 lbs

### TRANSMISSION

Type	Automatic
Gears	Allison 3000 6-speed

### FUEL

Type	Diesel
Fuel Tank	100 Gallon
Def Tank	13 Gallon

### SUSPENSION

Front	NEWAY
Wheel Cut	54 Degree front wheel
Rear	V-Ride

### SHOCKS

Make	Sachs custom tuned
------	--------------------

### AXLES

Front	Detroit DA-F-14.7-3
Rear	Detroit DA-RS-21.0-4
Tag	UltraSteer

### BRAKES

Front	Bendix Air Disc Brakes with ABS
Rear	Meritor Air Drum Brakes with ABS

### COOLING

Radiator	1,335 sq/inch, Rear mounted
----------	-----------------------------

### RAILS

Front	9.0" x 2.75" x 0.25"
Upper	9.0" x 2.75" x 0.25"
Rear	9.0" x 2.75" x 0.25"

### FRAME

Construction	Raised rail with lowered rear section
Wheel Base	245"

### HITCH

Rating	15,000 lbs
--------	------------

### TIRES

Make	Michelin XRV
Front Size	305/70R 22.5 20-ply
Rear Size	305/70R 22.5 20-ply
Tag Size	305/70R 22.5 20-ply
Wheels	8.25" Aluminum

### ELECTRICAL

Alternator	240 Amp Leece-Neville
Battery	(2) 1,900 CCA @ 0 degrees F

### CONTROLS

Steering Column	Column Drive with Tilt/Telescopic
Steering Wheel	DriveTech steering wheel with dash controls
Instruments	OptiView LCD display
Safety	Mobileye Sensor Detection

### WARRANTY

Basic Chassis / Drivetrain	5 years, 100,000 mi
Engine	5 years, 100,000 mi
Transmission	5 years, 200,000 mi
Battery	1 year, 100,000 mi
Corrosion / Brightwork	6 months unlimited
Frame Rails / Cross Member	5 years, 100,000 mi