



2023 SPEC SHEET

Newmar Kountry Star

Floor plans: 3412, 3426

5-STAR FEATURES



24/7 factory-direct phone support

BRAKE SYNC

Factory-installed, factory-warranted integrated air supply for your tow vehicle brake system

DRIVETECH

Wheel and column controls pair with OptiView to put every command in easy reach

All-new ergonomic steering wheel

Prioritizes driver safety

V RIDE

Increased towing capacity

Superior roll stability & handling

Greater durability & longevity

ENGINE

Make	Cummins B6.7
Horsepower	360 HP @ 2,600 rpm
Torque	800 lb/ft
Brake	VGT (Variable Geometry Turbocharger) Brake (single stage)

WEIGHT RATINGS

Front GAWR	12,400 lbs
Rear GAWR	21,000 lbs
Tag GAWR	N/A
Total GVWR	33,400 lbs
Total GCWR	43,400 lbs

TRANSMISSION

Type	Automatic
Gears	Allison 3000 6-speed

FUEL

Type	Diesel
Fuel Tank	100 Gallon
Def Tank	10 Gallon

SUSPENSION

Front	NEWAY
Wheel Cut	55 Degree front wheel
Rear	V-Ride

SHOCKS

Make	Sachs custom tuned
-------------	--------------------

AXLES

Front	Detroit DA-F-12.4-3
Rear	Detroit DA-RS-21.0-2

BRAKES

Front	Bendix Air Disc Brakes with ABS
Rear	Meritor Air Drum Brakes with ABS

COOLING

Radiator	1,335 sq/inch, Rear mounted
-----------------	-----------------------------

RAILS

Front	9.0" x 2.75" x 0.25"
Upper	9.0" x 2.75" x 0.25"
Rear	9.0" x 2.75" x 0.25"

FRAME

Construction	Raised rail with lowered rear section
Wheel Base	206"

HITCH

Rating	5,000 lbs
---------------	-----------

TIRES

Make	Michelin X Multi Z
Front Size	275/70R 22.5 18-ply
Rear Size	275/70R 22.5 18-ply
Wheels	8.25" Aluminum

ELECTRICAL

Alternator	160 Amp
Battery	(2) 1,900 CCA @ 0 degrees F

CONTROLS

Steering Column	Column Drive with Tilt/Telescopic
Steering Wheel	DriveTech steering wheel with dash controls
Instruments	OptiView LCD display
Safety	Mobileye Sensor Detection

WARRANTY

Basic Chassis / Drivetrain	5 years, 100,000 mi
Engine	5 years, 100,000 mi
Transmission	5 years, 200,000 mi
Battery	1 year, 100,000 mi
Corrosion / Brightwork	6 months unlimited
Frame Rails / Cross Member	5 years, 100,000 mi



2023 SPEC SHEET

Newmar Kountry Star

Floor plans: 3709, 3717

5-STAR FEATURES



24/7 factory-direct phone support

BRAKE SYNC

Factory-installed, factory-warranted integrated air supply for your tow vehicle brake system

DRIVETECH

Wheel and column controls pair with OptiView to put every command in easy reach

All-new ergonomic steering wheel
Prioritizes driver safety

V RIDE

Increased towing capacity
Superior roll stability & handling
Greater durability & longevity

ENGINE

Make	Cummins B6.7
Horsepower	360 HP @ 2,600 rpm
Torque	800 lb/ft
Brake	VGT (Variable Geometry Turbocharger) Brake (single stage)

WEIGHT RATINGS

Front GAWR	13,500 lbs
Rear GAWR	24,000 lbs
Tag GAWR	N/A
Total GVWR	37,500 lbs
Total GCWR	47,500 lbs

TRANSMISSION

Type	Automatic
Gears	Allison 3000 6-speed

FUEL

Type	Diesel
Fuel Tank	100 Gallon
Def Tank	10 Gallon

SUSPENSION

Front	NEWAY
Wheel Cut	54 Degree front wheel
Rear	V-Ride

SHOCKS

Make	Sachs custom tuned
-------------	--------------------

AXLES

Front	Detroit DA-F-14.7-3
Rear	Detroit DA-RS-23.0-4

BRAKES

Front	Bendix Air Disc Brakes with ABS
Rear	Bendix Air Drum Brakes with ABS

COOLING

Radiator	1,335 sq/inch, Rear mounted
-----------------	-----------------------------

RAILS

Front	9.0" x 2.75" x 0.25"
Upper	9.0" x 2.75" x 0.25"
Rear	9.0" x 2.75" x 0.25"

FRAME

Construction	Raised rail with lowered rear section
Wheel Base	242"

HITCH

Rating	5,000 lbs
---------------	-----------

TIRES

Make	Michelin XRV
Front Size	305/70R 22.5 18-ply
Rear Size	305/70R 22.5 18-ply
Wheels	8.25" Aluminum

ELECTRICAL

Alternator	160 Amp
Battery	(2) 1,900 CCA @ 0 degrees F

CONTROLS

Steering Column	Column Drive with Tilt/Telescopic
Steering Wheel	DriveTech steering wheel with dash controls
Instruments	OptiView LCD display
Safety	Mobileye Sensor Detection

WARRANTY

Basic Chassis / Drivetrain	5 years, 100,000 mi
Engine	5 years, 100,000 mi
Transmission	5 years, 200,000 mi
Battery	1 year, 100,000 mi
Corrosion / Brightwork	6 months unlimited
Frame Rails / Cross Member	5 years, 100,000 mi



2023 SPEC SHEET

Newmar Kountry Star

Floor plans: 4011, 4037, 4068, 4070

5-STAR FEATURES



24/7 factory-direct phone support

BRAKE SYNC

Factory-installed, factory-warranted integrated air supply for your tow vehicle brake system

DRIVETECH

Wheel and column controls pair with OptiView to put every command in easy reach

All-new ergonomic steering wheel

Prioritizes driver safety

V RIDE

Increased towing capacity

Superior roll stability & handling

Greater durability & longevity

ENGINE

Make	Cummins B6.7
Horsepower	360 HP @ 2,600 rpm
Torque	800 lb/ft
Brake	VGT (Variable Geometry Turbocharger) Brake (single stage)

WEIGHT RATINGS

Front GAWR	14,200 lbs
Rear GAWR	24,000 lbs
Tag GAWR	N/A
Total GVWR	38,200 lbs
Total GCWR	48,200 lbs

TRANSMISSION

Type	Automatic
Gears	Allison 3000 6-speed

FUEL

Type	Diesel
Fuel Tank	100 Gallon
Def Tank	10 Gallon

SUSPENSION

Front	NEWAY
Wheel Cut	54 Degree front wheel
Rear	V-Ride

SHOCKS

Make	Sachs custom tuned
-------------	--------------------

AXLES

Front	Detroit DA-F-14.7-3
Rear	Detroit DA-RS-23.0-4

BRAKES

Front	Bendix Air Disc Brakes with ABS
Rear	Bendix Air Drum Brakes with ABS

COOLING

Radiator	1,335 sq/inch, Rear mounted
-----------------	-----------------------------

RAILS

Front	9.0" x 2.75" x 0.25"
Upper	9.0" x 2.75" x 0.25"
Rear	9.0" x 2.75" x 0.25"

FRAME

Construction	Raised rail with lowered rear section
Wheel Base	276"

HITCH

Rating	5,000 lbs
---------------	-----------

TIRES

Make	Michelin XRV
Front Size	305/70R 22.5 20-ply
Rear Size	305/70R 22.5 20-ply
Wheels	8.25" Aluminum

ELECTRICAL

Alternator	160 Amp
Battery	(2) 1,900 CCA @ 0 degrees F

CONTROLS

Steering Column	Column Drive with Tilt/Telescopic
Steering Wheel	DriveTech steering wheel with dash controls
Instruments	OptiView LCD display
Safety	Mobileye Sensor Detection

WARRANTY

Basic Chassis / Drivetrain	5 years, 100,000 mi
Engine	5 years, 100,000 mi
Transmission	5 years, 200,000 mi
Battery	1 year, 100,000 mi
Corrosion / Brightwork	6 months unlimited
Frame Rails / Cross Member	5 years, 100,000 mi