





2024 SPEC SHEET

Newmar New Aire

Floor plans: 3539, 3543, 3549, 3547

STAR FFATURE



24/7 factory-direct phone support



7F Independent Front Suspension with up to 60-Degree Wheel Cut: the tightest turning radius in the industry

BRAKE 🖨 SYNC

Factory-installed, factory-warranted integrated air supply for your tow vehicle brake system

Wheel and column controls pair with OptiView to put every command in easy reach

All-new ergonomic steering wheel Prioritizes driver

safety

ROADWATCH

Suite of state-ofthe-art safety systems for driver confidence in all conditions and maneuvers



Increased towing capacity Superior roll stability & handling Greater durability

NI	c	IK	п	

Cummins L9 Make 450 HP @ 2,100 rpm Horsepower

1,250 lb-ft Torque

VGT (Variable Geometry Turbocharger) Brake (single stage) Brake

WEIGHT RATINGS

14,600 lbs Front GAWR Rear GAWR 24,000 lbs Tag GAWR N/Δ **Total GVWR** 38,600 lbs **Total GCWR** 48,600 lbs

TRANSMISSION

Type Automatic

Gears Allison 3000 6-speed

FUEL

Type Diesel 90 Gallon Fuel Tank Def Tank 15 Gallon

SUSPENSION

7F Front

Wheel Cut 60 Degree front wheel

V-Ride

SHOCKS

Sachs custom tuned Make

AXLES

Front

Detroit DA-RS-23.0-4 Rear

BRAKES

Bendix Air Disc Brakes with ABS Front Rear Bendix Air Drum Brakes with ABS

COOLING

Radiator 1,638 sq. in., Side mounted RAILS

Straight 9.125" x 2.81" x 0.3125"

FRAME

Straight rail with lowered rear section Construction

Wheel Base 226'

HITCH

5,000 lbs Rating

TIRES

Michelin XRV Make 305/70R 22.5 20-ply Front Size Rear Size 305/70R 22.5 20-ply

Wheels 9" Aluminum

ELECTRICAL

240 Amp Leece-Neville Alternator (2) 1,900 CCA @ 0 degrees F Battery

CONTROLS

Steering Column Column Drive with Tilt/Telescopic

Steering Wheel DriveTech steering wheel w/ OptiView controls

15" OptiView LCD with Roadwatch. Push Button Start and Tire Presssure Monitoring System Instruments

RoadWatch featuring Electronic Stability Control (ESC) with Roll Stability Support (RSS), Adaptive Cruise Control (ACC), Automatic Traction Control (ATC), Collision Mitigation (forward warning and active braking), Mobileye Sensor Detection

WARRANTY

Safety

Basic Chassis / Drivetrain

5 years, 100,000 mi

Engine 5 years, 100,000 mi **Transmission** 5 years, 200,000 mi

Battery 1 year, 100,000 mi Corrosion / 6 months unlimited

Brightwork

Frame Rails / 5 years, 100,000 mi

Cross Member