



2024 SPEC SHEET

Newmar Ventura

Floor plans: 3507, 3512

5-STAR FEATURES



24/7 factory-direct phone support

BRAKE SYNC

Factory-installed, factory-warranted integrated air supply for your tow vehicle brake system

DRIVETECH

Wheel and column controls pair with OptiView to put every command in easy reach

All-new ergonomic steering wheel

Prioritizes driver safety

ROADWATCH

Suite of state-of-the-art safety systems for driver confidence in all conditions and maneuvers

V-RIDE

Increased towing capacity

Superior roll stability & handling

Greater durability & longevity

ENGINE

Make	Cummins L9
Horsepower	380 HP @ 2,200 rpm
Torque	1,150 lb-ft
Brake	VGT (Variable Geometry Turbocharger) Brake (single stage)

WEIGHT RATINGS

Front GAWR	14,200 lbs
Rear GAWR	24,000 lbs
Tag GAWR	N/A
Total GVWR	38,200 lbs
Total GCWR	48,200 lbs

TRANSMISSION

Type	Automatic
Gears	Allison 3000 6-speed

FUEL

Type	Diesel
Fuel Tank	100 Gallon
Def Tank	10 Gallon

SUSPENSION

Front	VFS
Wheel Cut	55 Degree front wheel
Rear	V-Ride

SHOCKS

Make	Sachs custom tuned
-------------	--------------------

AXLES

Front	VFS 14.2
Rear	Detroit DA-RS-23.0-4

BRAKES

Front	Bendix Air Disc Brakes with ABS
Rear	Meritor Air Drum Brakes with ABS

COOLING

Radiator	1,335 sq. in., Rear mounted
-----------------	-----------------------------

RAILS

Front	9.0" x 2.75" x 0.25"
Upper	9.0" x 2.75" x 0.25"
Rear	9.0" x 2.75" x 0.25"

FRAME

Construction	Raised rail with lowered rear section
Wheel Base	212"

HITCH

Rating	5,000 lbs
---------------	-----------

TIRES

Make	Michelin XRV
Front Size	305/70R 22.5 20-ply
Rear Size	305/70R 22.5 20-ply
Wheels	9" Aluminum

ELECTRICAL

Alternator	240 Amp Leece-Neville
Battery	(2) 1,900 CCA @ 0 degrees F

CONTROLS

Steering Column	Column Drive with Tilt/Telescopic
Steering Wheel	DriveTech steering wheel with dash controls
Instruments	OptiView LCD display and TPMS
Safety	RoadWatch featuring Mobileye Sensor Detection, Automatic Traction Control (ATC), Electronic Stability Control (ESC) with Roll Stability Support (RSS), Adaptive Cruise Control (ACC), Collision Mitigation (forward warning and active braking)

WARRANTY

Basic Chassis / Drivetrain	5 years, 100,000 mi
Engine	5 years, 100,000 mi
Transmission	5 years, 200,000 mi
Battery	1 year, 100,000 mi
Corrosion / Brightwork	6 months unlimited
Frame Rails / Cross Member	5 years, 100,000 mi



2024 SPEC SHEET

Newmar Ventana

Floor plans: 3809, 3817

5-STAR FEATURES



24/7 factory-direct phone support

BRAKE SYNC

Factory-installed, factory-warranted integrated air supply for your tow vehicle brake system

DRIVETECH

Wheel and column controls pair with OptiView to put every command in easy reach

All-new ergonomic steering wheel

Prioritizes driver safety

ROADWATCH

Suite of state-of-the-art safety systems for driver confidence in all conditions and maneuvers

V-RIDE

Increased towing capacity

Superior roll stability & handling

Greater durability & longevity

ENGINE

Make	Cummins L9
Horsepower	380 HP @ 2,200 rpm
Torque	1,150 lb-ft
Brake	VGT (Variable Geometry Turbocharger) Brake (single stage)

WEIGHT RATINGS

Front GAWR	15,000 lbs
Rear GAWR	24,000 lbs
Tag GAWR	N/A
Total GVWR	39,000 lbs
Total GCWR	49,000 lbs

TRANSMISSION

Type	Automatic
Gears	Allison 3000 6-speed

FUEL

Type	Diesel
Fuel Tank	100 Gallon
Def Tank	10 Gallon

SUSPENSION

Front	VFS
Wheel Cut	51 Degree front wheel
Rear	V-Ride

SHOCKS

Make	Sachs custom tuned
-------------	--------------------

AXLES

Front	VFS 15.0
Rear	Detroit DA-RS-23.0-4

BRAKES

Front	Bendix Air Disc Brakes with ABS
Rear	Bendix Air Drum Brakes with ABS

COOLING

Radiator	1,335 sq. in., Rear mounted
-----------------	-----------------------------

RAILS

Front	9.0" x 2.75" x 0.25"
Upper	9.0" x 2.75" x 0.25"
Rear	9.0" x 2.75" x 0.25"

FRAME

Construction	Raised rail with lowered rear section
Wheel Base	248"

HITCH

Rating	5,000 lbs
---------------	-----------

TIRES

Make	Michelin XRV
Front Size	295/80R 22.5 20-ply
Rear Size	295/80R 22.5 20-ply
Wheels	9" Aluminum

ELECTRICAL

Alternator	240 Amp Leece-Neville
Battery	(2) 1,900 CCA @ 0 degrees F

CONTROLS

Steering Column	Column Drive with Tilt/Telescopic
Steering Wheel	DriveTech steering wheel with dash controls
Instruments	OptiView LCD display and TPMS
Safety	RoadWatch featuring Mobileye Sensor Detection, Collision Mitigation (forward warning and active braking), Electronic Stability Control (ESC) with Roll Stability Support (RSS), Adaptive Cruise Control (ACC), Automatic Traction Control (ATC)

WARRANTY

Basic Chassis / Drivetrain	5 years, 100,000 mi
Engine	5 years, 100,000 mi
Transmission	5 years, 200,000 mi
Battery	1 year, 100,000 mi
Corrosion / Brightwork	6 months unlimited
Frame Rails / Cross Member	5 years, 100,000 mi



2024 SPEC SHEET

Newmar Ventura Tag

Floor plans: 4037, 4068

5-STAR FEATURES



24/7 factory-direct phone support

BRAKE SYNC

Factory-installed, factory-warranted integrated air supply for your tow vehicle brake system

DRIVETECH

Wheel and column controls pair with OptiView to put every command in easy reach

All-new ergonomic steering wheel

Prioritizes driver safety

ROADWATCH

Suite of state-of-the-art safety systems for driver confidence in all conditions and maneuvers

ULTRA STEER

Reduced curb-to-curb turning radius

Eliminates costly tire scrub

Fully integrated & precision tuned to coach model & floorplan

V RIDE

Increased towing capacity

Superior roll stability & handling

Greater durability & longevity

ENGINE

Make	Cummins L9
Horsepower	400 HP @ 2,100 rpm
Torque	1,250 lb-ft
Brake	Engine Compression Brake (three stage)

WEIGHT RATINGS

Front GAWR	15,000 lbs
Rear GAWR	20,000 lbs
Tag GAWR	10,000 lbs
Total GVWR	45,000 lbs
Total GCWR	60,000 lbs

TRANSMISSION

Type	Automatic
Gears	Allison 3000 6-speed

FUEL

Type	Diesel
Fuel Tank	100 Gallon
Def Tank	13 Gallon

SUSPENSION

Front	VFS
Wheel Cut	51 Degree front wheel
Rear	V-Ride

SHOCKS

Make	Sachs custom tuned
-------------	--------------------

AXLES

Front	VFS 15.0
Rear	Detroit DA-RS-21.0-4
Tag	UltraSteer

BRAKES

Front	Bendix Air Disc Brakes with ABS
Rear	Meritor Air Drum Brakes with ABS

COOLING

Radiator	1,335 sq. in., Rear mounted
-----------------	-----------------------------

RAILS

Front	9.0" x 2.75" x 0.25"
Upper	9.0" x 2.75" x 0.25"
Rear	9.0" x 2.75" x 0.25"

FRAME

Construction	Raised rail with lowered rear section
Wheel Base	245"

HITCH

Rating	15,000 lbs
---------------	------------

TIRES

Make	Michelin XRV
Front Size	295/80R 22.5 20-ply
Rear Size	295/80R 22.5 20-ply
Tag Size	295/80R 22.5 20-ply
Wheels	9" Aluminum

ELECTRICAL

Alternator	240 Amp Leece-Neville
Battery	(2) 1,900 CCA @ 0 degrees F

CONTROLS

Steering Column	Column Drive with Tilt/Telescopic
Steering Wheel	DriveTech steering wheel with dash controls
Instruments	OptiView LCD display and TPMS
Safety	RoadWatch featuring Mobileye Sensor Detection, Collision Mitigation (forward warning and active braking), Adaptive Cruise Control (ACC), Electronic Stability Control (ESC) with Roll Stability Support (RSS), Automatic Traction Control (ATC)

WARRANTY

Basic Chassis / Drivetrain	5 years, 100,000 mi
Engine	5 years, 100,000 mi
Transmission	5 years, 200,000 mi
Battery	1 year, 100,000 mi
Corrosion / Brightwork	6 months unlimited
Frame Rails / Cross Member	5 years, 100,000 mi



2024 SPEC SHEET

Newmar Ventura Tag

Floor plans: 4326, 4369, 4310, 4328

5-STAR FEATURES



24/7 factory-direct phone support

BRAKE SYNC

Factory-installed, factory-warranted integrated air supply for your tow vehicle brake system

DRIVETECH

Wheel and column controls pair with OptiView to put every command in easy reach

All-new ergonomic steering wheel

Prioritizes driver safety

ROADWATCH

Suite of state-of-the-art safety systems for driver confidence in all conditions and maneuvers

ULTRA STEER

Reduced curb-to-curb turning radius

Eliminates costly tire scrub

Fully integrated & precision tuned to coach model & floorplan

V RIDE

Increased towing capacity

Superior roll stability & handling

Greater durability & longevity

ENGINE

Make	Cummins L9
Horsepower	400 HP @ 2,100 rpm
Torque	1,250 lb-ft
Brake	Engine Compression Brake (three stage)

WEIGHT RATINGS

Front GAWR	15,600 lbs
Rear GAWR	20,000 lbs
Tag GAWR	10,000 lbs
Total GVWR	45,600 lbs
Total GCWR	60,600 lbs

TRANSMISSION

Type	Automatic
Gears	Allison 3000 6-speed

FUEL

Type	Diesel
Fuel Tank	100 Gallon
Def Tank	13 Gallon

SUSPENSION

Front	VFS
Wheel Cut	51 Degree front wheel
Rear	V-Ride

SHOCKS

Make	Sachs custom tuned
-------------	--------------------

AXLES

Front	VFS 15.6
Rear	Detroit DA-RS-21.0-4
Tag	UltraSteer

BRAKES

Front	Bendix Air Disc Brakes with ABS
Rear	Meritor Air Drum Brakes with ABS

COOLING

Radiator	1,335 sq. in., Rear mounted
-----------------	-----------------------------

RAILS

Front	9.0" x 2.75" x 0.25"
Upper	9.0" x 2.75" x 0.25"
Rear	9.0" x 2.75" x 0.25"

FRAME

Construction	Raised rail with lowered rear section
Wheel Base	281"

HITCH

Rating	15,000 lbs
---------------	------------

TIRES

Make	Michelin X Line Energy Z
Front Size	315/80R 22.5 20-ply
Rear Size	315/80R 22.5 20-ply
Tag Size	315/80R 22.5 20-ply
Wheels	9.00" Aluminum

ELECTRICAL

Alternator	240 Amp Leece-Neville
Battery	(2) 1,900 CCA @ 0 degrees F

CONTROLS

Steering Column	Column Drive with Tilt/Telescopic
Steering Wheel	DriveTech steering wheel with dash controls
Instruments	OptiView LCD display and TPMS
Safety	RoadWatch featuring Mobileye Sensor Detection, Adaptive Cruise Control (ACC), Collision Mitigation (forward warning and active braking), Automatic Traction Control (ATC), Electronic Stability Control (ESC) with Roll Stability Support (RSS)

WARRANTY

Basic Chassis / Drivetrain	5 years, 100,000 mi
Engine	5 years, 100,000 mi
Transmission	5 years, 200,000 mi
Battery	1 year, 100,000 mi
Corrosion / Brightwork	6 months unlimited
Frame Rails / Cross Member	5 years, 100,000 mi