





2025 SPEC SHEET

Newmar London Aire Tag

Floor plans: 4535, 4551, 4569, 4595

5-STAR FEATURES



247

24/7 factory-direct phone support



ZF Independent Front Suspension with up to 60-Degree Wheel Cut: the tightest turning radius in the industry



Factory-installed, factory-warranted integrated air supply for your tow vehicle brake system

DRIVETECH

Wheel and column controls pair with OptiView to put every command in easy reach

All-new ergonomic steering wheel

Prioritizes driver safety

ROADWATCH

Suite of state-ofthe-art safety systems for driver confidence in all conditions and maneuvers

ULTRASTEER

Reduced curb-tocurb turning radius Eliminates costly

Fully integrated & precision tuned to coach model & floorplan

tire scrub



Increased towing capacity

Superior roll stability & handling

Greater durability & longevity

Make Cummins X15

Horsepower 605 HP @ 1,800 rpm

Torque 1,950 lb-ft

Brake Engine Compression Brake (three stage)

WEIGHT RATINGS

 Front GAWR
 20,000 lbs

 Rear GAWR
 20,000 lbs

 Tag GAWR
 14,000 lbs

 Total GVWR
 54,000 lbs

 Total GCWR
 74,000 lbs

TRANSMISSION

Type Automatic

Gears Allison 4000 6-speed

FUEL

Type Diesel
Fuel Tank 150 Gallon
Def Tank 15 Gallon

SUSPENSION

Front Z

Wheel Cut 52 Degree front wheel

Rear V-Ride

SHOCKS

Make Sachs custom tuned

AXLES

Front Z

Rear Detroit DA-RC-24.0-6

Tag UltraSteer

BRAKES

Front Bendix Air Disc Brakes with ABS

Rear Bendix Air Disc Brakes with ABS

COOLING

Radiator 1,761 sq. in., Side mounted

RAILS

 Front
 11.0" x 3.0" x 0.3125"

 Upper
 9.5" x 3.0" x 0.3125"

 Rear
 10.0" x 3.0" x 0.3125"

FRAME

Construction Raised rail w/ heavy duty lowered rear section

Wheel Base 292"

HITCH

Rating 20,000 lbs

TIRES

 Make
 Michelin XZA

 Front Size
 365/70R 22.5 20-ply

Rear Size 315/80R 22.5 **Tag Size** 315/80R 22.5

Wheels 10.5" FR/ 9" RR Aluminum

ELECTRICAL

Alternator 270 Amp Leece-Neville

Battery (2) 1,900 CCA @ 0 degrees F

CONTROLS

Steering Column Column Drive with Tilt/Telescopic

 Steering Wheel
 DriveTech steering wheel w/ dash controls

 Instruments
 OptiView LCD display w/ Roadwatch/TPMS

Safety Mobileye Sensor Detection

RoadWatch featuring Automatic Traction Control (ATC), Collision Mitigation (forward warning and active braking), Electronic Stability Control (ESC) with Roll Stability Support (RSS), Adaptive Cruise

Control (ACC),

WARRANTY

Basic Chassis / Drivetrain 5 years, 100,000 mi

Engine 5 years, 100,000 mi
Transmission 5 years, 200,000 mi
Battery 1 year, 100,000 mi
Corrosion / 6 months unlimited
Brightwork

Frame Rails / Cross Member 5 years, 100,000 mi